

DATAMAX[®] M450

2D Linear-Imaging Barcode Scanner

多场景覆盖 使用便捷

适用于商超、餐饮、专卖店等行业



Performance Parameter	
Image (pixels)	640 pixels(H)*480 pixels(V)
Light Source	Aiming:617 nm LED ; Illumination:6500K LED
Scanning Distance	40-200mm @ UPC/EAN 13mil PCS=90%; 20-250mm @ QR 20mil PCS=100%
Image Resolution	≥ 5mil
Minimum Print Contrast	≥ 25% (UPC/EAN 100%)
Barcode Sensitivity	Pitch ±65°
	Roll ±30°
	Skew ±55°
Barcode Types	1D: UPC/EAN/JAN,UPC-A & UPC-E,EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93,Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code,MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode), RSS 14,RSS Limited, RSS Expanded 2D: QR Code, Data Matrix, PDF417 etc.
Mechanical and Electric Performance	
SIZE(Length x Width x Height)	165mm*67mm*94mm
Weight (without cable)	173g
Indicator	Beeper and LED Light
Communication interface	HID USB、USB Virtual COM、RS-232
Input voltage	5VDC±10%
Working Current	300mA
Environmental Parameter	
Storage Temperature	-40°C ~ 60°C
Working Temperature	0°C ~ 50°C
Relative Humidity	5% ~ 95%
Drop Resistance	5M
IP Rating	IP52
Certificates	
CE,RoHS,EMC,LVD, ISO9001:2008, ISO14001:2004	

手感舒适

按键采用符合人体工学设计，触点式按钮，线条较短，不再出现卡住或者黏住的现象。手感舒适，不易疲劳，适合长时间操作



支持自动感应

配备扫描枪支架更高效
支架需另外购买



即插即用 免软件安装

兼容WindowsXP、7、8、10、Vista等版本系统，兼容台式机、笔记本、收银机各个终端，USB通用数据传输线。



高端工艺压铸扫描头

采用合金压铸工艺：精准定位光学组件，坚固金属外壳保护光学部件内部支架设计；牢固解码线路板和条码引擎，保证性能的稳定性

