




Desktop Printers

## DT2x / DT4x

Discover how powerful a Simple of Compact Barcode Printer can be.

DT2x / DT4x are both ultra-light, compact for best space utilization and support multiple communication ports; they are effective and multitasking for printing retail, warehouses, logistic & transportation, health care labels and tags.



Enhanced label feeding mechanism and instant label detection.



- 16MB SDRAM and 4 / 8 MB Flash memory- including 2 / 4 MB user-available memory storage for downloadable objects.
- Print speed: Up to 7"/177 mm per second
- Supports Ethernet, Serial and USB ports.

# GoDEX

# Specification

## DT2x / DT4x

### Desktop Printer

| Model                                    | DT2x  | DT4x  |
|--|---|---|
| <b>Print Method</b>                      | Direct Thermal  |   |
| <b>Resolution</b>                        | 203 dpi (8 dots/mm)   |   |
| <b>Print Speed</b>                       | 7 IPS (177 mm/s)**  |   |
| <b>Print Width</b>                       | 2.12" (54 mm)   | 4.25" (108 mm)  |
| <b>Print Length</b>                      | Min. 0.16" (4 mm)**; Max. 68" (1727 mm)   |   |
| <b>Processor</b>                         | 32 Bit RISC CPU   |   |
| <b>Memory Flash</b>                      | 4 MB Flash (2 MB for user storage)  | 8 MB Flash (4 MB for user storage)  |
| <b>SDRAM</b>                             | 16 MB   |   |
| <b>Sensor Type</b>                       | Adjustable reflective sensor. Fixed transmissive sensor, central aligned.   | Adjustable reflective sensor. Fixed transmissive sensor, central aligned. |
| <b>Media Types</b>                       | Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming  |   |
| <b>Width</b>                             | Min. 0.6" (15 mm) – Max. 2.36" (60 mm)  | Min. 1" (25.4 mm) – Max. 4.64" (118 mm)                                   |
| <b>Thickness</b>                         | Min. 0.003" (0.076 mm) – Max. 0.008" (0.20 mm)  |   |
| <b>Label Roll Diameter</b>               | Max. 5" (127 mm)  |   |
| <b>Core Diameter</b>                     | 1" (25.4 mm), 1.5" (38.1mm)   |   |
| <b>Printer Language</b>                  | EZPL, GEPL, GZPL, GDPL auto switch  |   |
| <b>Software Label Design Software</b>    | GoLabel (for EZPL only)   |   |
| <b>Driver</b>                            | Vista, Windows 7, Windows 8 & 8.1, Windows 10, Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019, MAC, Linux Win CE, .NET, Windows Vista, Windows 7, Windows 8 & 8.1, Windows 10, Android, Mac, iOS   |   |
| <b>Resident Fonts Bitmap Fonts</b>       | 6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B<br>Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable<br>Bitmap fonts 8 times expandable in horizontal and vertical directions   |   |
| <b>TTF Fonts</b>                         | TTF Fonts (Bold / Italic / Underline ). 0°,90°, 180°, 270° rotatable  |   |
| <b>Download Fonts Bitmap Fonts</b>       | 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable  |   |
| <b>Asian Fonts</b>                       | 16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese(GB2312), Japanese (S-JIS), Korean (KS-X1001)<br>90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions  |   |
| <b>TTF Fonts</b>                         | TTF Fonts (Bold / Italic / Underline ). 0°,90°, 180°, 270° rotatable  |   |
| <b>Barcodes 1-D Bar codes</b>            | China Postal Code, Codabar, Code 11, Code 32,Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5 , Interleaved 2-of-5 (1 2 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K-Mart and Random Weight |   |
| <b>2-D Bar codes</b>                     | Aztec code, Code 49,Codablock F , Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417,QR code, TLC 39, GS1 Composite   |   |
| <b>Code Pages</b>                        | CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737<br>WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257<br>Unicode UTF8 \ UTF16BE \ UTF16LE   |   |
| <b>Graphics</b>                          | Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software   |   |
| <b>Interfaces</b>                        | USB 2.0 (B-Type)<br>Serial port: RS-232 (DB-9)<br>IEEE 802.3 10 / 100 Base-Tx Ethernet port (RJ-45)   |   |
| <b>Control Panel</b>                     | One Tri-color LED : Power (Green, Orange and Red)<br>Function Key : FEED  |   |
| <b>Power</b>                             | Auto Switching 100-240V AC, 50-60Hz.  |   |
| <b>Real Time Clock</b>                   | Standard  |   |
| <b>Environment Operation Temperature</b> | 41°F to 104°F (5°C to 40°C)   |   |
| <b>Storage Temperature</b>               | -4°F to 122°F (-20°C to 50°C)   |   |
| <b>Humidity Operation</b>                | 30-85%, non-condensing.   |   |
| <b>Storage</b>                           | 10-90%, non-condensing.   |   |
| <b>Agency Approvals</b>                  | CE(EMC) \ FCC Class A \ CB \ cUL \ EAC \ KCC \ CCC  |   |
| <b>Dimension Length</b>                  | 8.58" (218 mm)  | 8.58" (218 mm)  |
| <b>Height</b>                            | 6.77" (172 mm)  | 6.53" (166 mm)  |
| <b>Width</b>                             | 3.94" (100 mm)  | 6.61" (168 mm)  |
| <b>Weight</b>                            | 2.25 lbs (1.07 Kg) ,excluding consumables   | 3.17 lbs (1.44 Kg) ,excluding consumables                                 |
| <b>Options &amp; Accessories</b>         | Cutter module<br>Label Dispenser<br>External label roll holder for 10" (250 mm) O.D. label rolls<br>External label rewinder   |   |

\*\*Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.



winpoint.com.hk

永邦系統  
**WINPOINT**  
S Y S T E M S