

EC Thermal Receipt Printer

True value in POS

EC80330

Features

- Fast 300 mm/s printing speed
- ESC/POS & START command sets compatible
- Interface: serial +USB+100M Ethernet standard, Parallel+USB optional
- 100M network interface card make connection and print more faster
- Support 2D barcode printing
- Standard simplified / traditional Chinese characters library
- Built-in large data buffer
- Support network printing status monitoring, computer multiple connection
- Windows driver, Linux driver, OPOS driver available



Specifications

Print method
Print width
Dot density
Print speed
Interface
Paper diameter
Line space

Direct thermal line
64/76mm
512/576dot/line
300mm/s
Serial+USB+Ethernet, USB+Parallel
83mm
3.75mm(can be adjustable)

Character Size

ANK Font Font A: 12×24dots Font B: 9×17dots
Simplified/Traditional Chinese Character: 24×24dots

Code page

PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/
Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/
PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/
1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/
(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)

Barcode mode

UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/
CODABAR/CODE93/CODE128/QRCODE/PDF417

Fonts
BufferData
NV Flash
PowerCashdrawer out
Power supply
Weight
Dimension
Work environment
Storage environment
Reliability- Mechanism
Reliability-Auto Cutter
MTBF

GB18030
128K bytes
256K bytes
DC 24V/1A
AC 110V/220V, 50 ~ 60Hz, DC 24V/2A
1.23kg
180×139×127mm
Temperature:0 ~ 44°C, Humidity:10 ~ 80%
Temperature:-10 ~ 60°C, Humidity:10 ~ 90%
>150km
2 Million Cuts
360,000 Hours

